Improved DC Battery Backup Wall Mount Wi-Fi Garage Door Opener, Space-Saving, no Cable Tension Monitor, Heavy Lifting, LED Lighting System.

98022



- Space-saving design opens up the ceiling.
- Built-in Wi-FI and Bluetooth for the easiest way to connect the garage.
- myQ Remote LED Light provides maintenance-free illumination.
- myQ Mobile App lets users receive alerts and control the opener from anywhere

Quiet Operation

Wall-Mount design and a powerful ultra-quiet DC motor that eliminates noise and reduces vibrations through the ceiling while

providing a reliable, smooth operation.

Specifications

Motor

Medium-Duty 12V DC, automatic thermal protection, permanent lubrication

More Value Less Parts

 No more Cable Tension Monitor means faster and easier installation

Mechanics

- · Steel chassis and Plastic Cover
- Internal Chain and Sproket Drive Mechanism (63:1 Gear Reduction)
- · Auto-Force Adjustment for Changing Weather and Environmental Conditions
- . DC Wi-Fi logic with built-in Bluetooth and surge suppressor
- · Up to 850lbs lift capacity

Power

UL Listed, 6' power cord (3-prong)

120V AC, 60 Hz voltage, 1.5A current rating,

Speed

8.5" per second upward, 7.6" per second downward

Dimensions

Opener head: 21.5" H x 7.5" W x 7.9" L

myQ remote LED Light - 1,500 lumens

- · Max. Door Height: 14ft.
- · Max. Door Width: 18ft
- · Headroom clearance required:
 - 3in from Center of Torsion Bar
- · Max. Door Weight: 850lbs

Warranties

Lifetime: Motor 5 Year: Parts

1 Year: Battery and Accessories

Reliable

- Integrated Battery backup ensures access even when the powers out.
- Unmatched warranty that includes lifetime motor, 5-year parts, and 1-year battery and accessories.

- Time-to-Close automatically closes the door

Safe and Secure

- after a user defined amount of time: 1min, 5min, 10min or custom.
- Security+ 2.0 safeguards garage access by sending a new code to your garage door opener with every click.
- Motion Detector automaically turns on the light.
- The Protector System Auto-Reverses the Door if there's an obstruction.

Security+ 2.0 Radio controls:

Operating range ~200'; Operating temperature: -31°F to 149°F; 3-Button Remote Control (893MAX), Remote Control Code Format: Security+ 2.0, premium remote control; Garage Door Opener Code Format: Security+ 2.0; Anti-burglary coding.

Encrypted controls:

Smart Control Panel (880 LMW), Timer-to-Close, Program Remote Controls, Keypads and myQ accessories, Maintenance Alert System, Easy Wi-Fi Setup.

myQ Radio

902-928 MHz 50-Channel FHSS (frequently hopping spread spectrum); Provides 2-way communication from garage door opener and myQ accessories; enables monitoring and control of garage door openers via smartphone or tablet.

HomeLink® compatible (version 4.0 or higher) May require an external adapter depending on the model and year of vehicle. Visit HomeLink.com for additional information.

Pallet Shipping Weight

Qty 24 Units = 933lbs.

Carton (1)

Carton1: 28" L x 11.9" W x 11.9" H 38lbs.

- Garage Door Opener Head (98022)
- Smart Control Panel (880LMW)
- 3-Button Remote Control (893MAX)
- Automatic Garage Door Lock (841LM) - myQ Remote LED Light (827M)